

應用於鐵管類

GB-160CS / GB-262 GB-160-R

金屬拋光專用機系列 (曲型)

■ GB-262



■ GB-160CS



MODEL	型 式	GB-160CS	GB-262
Minimum diameter of work	最小砂光直徑	ø10 mm	—
Maximum diameter of work	最大砂光直徑	ø40 mm	—
Processing diameter	砂光直徑範圍	ø13-20 mm	—
Minimum curvature of work	最小工件曲型	R 160 mm	R 90 mm
Sanding belt size	砂帶尺寸	30 x 586 mm	13 x 262 mm
Sanding belt motor	砂帶驅動馬力	2 HP(4P)	1/2 HP(4P)
Disk drive motor	圓盤驅動馬力	2 HP(4P)	—
Machine dimension(LxWxH)	機械尺寸	500 x 650 x 1200 mm	440 x 420 x 1160 mm
Packing dimension(LxWxH)	裝箱尺寸	750 x 900 x 1550 mm	690 x 670 x 1510 mm
Net/Gross weight	淨重/毛重	180/220 kgs	72/122 kgs

MODEL	型 式	GB-160-R
Max. working diameter	最大加工直徑	120 mm
Min. working diameter	最小加工直徑	10 mm
Min. working length	最短加工長度	350 mm
Sanding head number	砂光座	1 set
Sanding belt size	砂帶尺寸	76 x 1285 (1270) mm
Sanding belt motor	砂帶驅動馬達	3 HP(5 HP)
Sanding belt speed(by inverter)	砂帶速度	Variable
Feeding head number(Conveyor drive)	送料座(輸送帶)	1 set
Feeding motor	送料馬力	1/2 HP x 1/40
Feeding speed(by inverter)	送料速度	2-25m/min Variable
Machine diameter(L x W x H)	機械尺寸	850 x 800 x 1200 mm
Packing diameter(L x W x H)	包裝尺寸	1000 x 950 x 1500 mm
Net/Gross weight	淨重/毛重	180/270 kgs



■ GB-160-R



■ GB-160-2R



■ GB-160-3R



■ GB-160-4R

MODEL	型 式	GB-160-2R	GB-160-3R	GB-160-4R
Max. working diameter	最大加工直徑	120 mm	120 mm	120 mm
Min. working diameter	最小加工直徑	10 mm	10 mm	10 mm
Min. working length	最短加工長度	350 mm	350 mm	350 mm
Sanding head number	砂光座	1 set	2 set	1 set
Sanding belt size	砂帶尺寸	76 x 1285 (1270) mm	76 x 1285 (1270) mm	76 x 1285 (1270) mm
Sanding belt motor	砂帶驅動馬達	3 HP(5 HP)	3 HP x 2(5 HP) x 2	3 HP x 3(5 HP) x 3
Sanding belt speed(by inverter)	砂帶速度	Variable	Variable	Variable
Feeding head number(Conveyor drive)	送料座(輸送帶)	2 sets	3 sets	4 sets
Feeding motor	送料馬力	(1/2 HP x 1/40) x 2	(1/2 HP x 1/40) x 2	(1/2 HP x 1/40) x 2
Feeding speed(by inverter)	送料速度	2-25m/min Variable	2-25m/min Variable	2-25m/min Variable
Machine diameter(L x W x H)	機械尺寸	1050 x 850 x 1350 mm	1600 x 950 x 1450 mm	2500 x 950 x 1450 mm
Packing diameter(L x W x H)	包裝尺寸	1200 x 1000 x 1500 mm	1700 x 1050 x 1550 mm	2600 x 1050 x 1550 mm
Net/Gross weight	淨重/毛重	250/450 kgs	1000/1200 kgs	1550/1700 kgs



■ GB-150



■ GB-250



■ GB-350

MODEL	型 式	GB-150	GB-250	GB-350
Range of work diameter	加工直徑範圍	ø10~ø60 mm(220 mm)	ø10~ø60 mm(220 mm)	ø10 to ø 60mm
Minimum length of work	最短工件長度	30mm~unlimited	200mm~unlimited	200mm~無限長unlimited
Sanding belt size	砂帶尺寸	125 x 1860 mm(5" x 73")	125 x 1860 mm(5" x 73")	2 1/2"X73"
Sanding belt motor	砂帶驅動馬力	3HP	5 HP	5HP(7 1/2 選配)
Suction motor	吸塵馬力	1/2HP	1/2 HP	1/2HP
Sanding belt speed	砂帶速度	18 m/sec	18 m/sec	18 m/sec
Feed speed	送料速度	6-20 m/min	6-20 m/min	4-15m/min
Machine dimension (LxWxH)	機械尺寸	750 x 510 x 1280 mm	950 x 650 x 1340 mm	950 x 680 x 1340 mm
Packing dimension (LxWxH)	裝箱尺寸	1000 x 760 x 1630 mm	1200 x 900 x 1690 mm	1200 x 950 x 1690 mm
Net/Gross weight	淨重/毛重	320 / 360 kgs	490 / 550 kgs	510 / 560 kgs



金照盛機械廠有限公司
CHIN CHAO SHENG MACHINERY CO., LTD.

427 台灣台中縣潭子鄉祥和路17號

427 NO.17 HSIANG HO ROAD., TAN TZE TAICHUNG TAIWAN.

TEL:04-2536 2737 • 2537 6697

FAX:04-2537 8926

E-mail:client@kcs-sander.com.tw

http://www.kcs-sander.com.tw